

LIQUID CRYSTAL DISPLAY DEVICE


Patent number: JP59195627
Publication date: 1984-11-06
Inventor: YAMADA HIDETOSHI; YUNOKI YUTAKA; KIMURA KENJI
Applicant: OLYMPUS OPTICAL CO
Classification:
- **international:** G09G3/18; G02F1/133; G09G3/18; G02F1/13; (IPC1-7): G02F1/133; G09G3/18
- **europaen:**
Application number: JP19830070643 19830421
Priority number(s): JP19830070643 19830421

Report a data error here

Abstract of JP59195627

PURPOSE: To obtain a good gradation display characteristics over a wide temperature range and to obtain a liquid crystal display device proper to an electronic view finder or the like for a portable apparatus by removing a variation component of incident light amount included in an electric signal and controlling effective voltage to be applied so as to hold the size of the signal at a fixed value.

CONSTITUTION: A photodetector 21 outputs a signal V_o proportional to the intensity of light transmitted through a liquid crystal layer 1. When voltage VSR applied to transparent electrodes 15, 16 is extremely high for a using temperature, $V_o > V_{ref}$ is formed and a signal for reducing the VSR is applied from a comparator 24 to a power supply 26. Consequently, the applied voltage is suppressed and the VSR is set up so that $I_t = 50\%$ is formed. When the VSR is extremely low, $V_o < V_{ref}$ is formed and a signal for increasing the VSR is applied to the power supply 26. Thus, the VSR is controlled to an optimum value in accordance with the using temperature. Simultaneously, voltage V_s to be applied to a display cell 11 is also controlled so that the most preferable gradation characteristics can be obtained.



Data supplied from the esp@cenet database - Worldwide